according to Regulation (EC) No 1907/2006

BEECK Interior Stand Oil Paint

Print date: 19.03.2018 Product code: FWB_B42 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

BEECK Interior Stand Oil Paint

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Resin stand oil lacquer for interior.

The product is to be used exclusively for the applications named in the technical data sheet or in the processing instructions.

1.3. Details of the supplier of the safety data sheet

Company name: BEECK'SCHE FARBWERKE GmbH

Street: Gottlieb-Daimler-Strasse 4
Place: D-89150 Laichingen

Telephone: +49 (0) 7333 / 9607-11 Telefax: +49 (0) 7333 / 9607-10

e-mail: info@beeck.com

Contact person: Ralf Rieks Telephone: +49 (0) 7333 / 9607-14

e-mail: Ralf.Rieks@beeck.com
Internet: www.beeck.com

Responsible Department: Factory Laichingen, Gottlieb-Daimler-Str. 4, D-89150 Laichingen

Tel. +49(0)7333/9607-11 Fax: +49(0)7333/9607-10 Mo-Fr: 8.00 -16.00 hour

1.4. Emergency telephone United Kingdom +44 870 600 626 / 0870 600 6266

number: GBK Gefahrgut Büro GmbH

+49(0)6132/84463

Further Information

No more data.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC

This mixture is not classified as hazardous according to Directive 1999/45/EC.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing.

P273 Avoid release to the environment.

P501 Disposal in accordance with the official regulations.

Special labelling of certain mixtures

EUH208 Contains Orange oil . May produce an allergic reaction.

according to Regulation (EC) No 1907/2006

BEECK Interior Stand Oil Paint

Print date: 19.03.2018 Product code: FWB_B42 Page 2 of 9

2.3. Other hazards

May cause sensitisation of susceptible persons.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
236-675-5	Titanium oxide	25 - < 30 %
13463-67-7		-
271-369-5	Hydrocarben, C11-C14, isoalkanes, cyclic < 2% aromatics	15 - < 20 %
68551-19-9	Xn - Harmful R65-66	
	Asp. Tox. 1; H304 EUH066	
01-2119480162-45		
	Calcium carbonate	5 - < 10 %
1317-65-3		
271-366-9	Isoalkanes, C10-13	1 - < 5 %
68551-17-7	Xn - Harmful R65-66	
	Asp. Tox. 1; H304	
265-150-3	Naphtha, low boiling point, treated with hydrogen	1 - < 5 %
64742-48-9	Xn - Harmful R65-66	
	Asp. Tox. 1; H304 EUH066	
238-877-9	Talcum	1 - < 5 %
14807-96-6		
232-433-8	Orange oil	< 1 %
8028-48-6	Xn - Harmful, Xi - Irritant, N - Dangerous for the environment R10-38-43-50-53-65	
	Flam. Liq. 3, Skin Irrit. 2, Skin Sens. 1, Asp. Tox. 1, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1 (M-Factor = 1); H226 H315 H317 H304 H400 H410	
01-2119493353-35		

Full text of R-, H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Show this safety data sheet to the doctor in attendance. Never give anything by mouth to an unconscious person. Lay the affected person down and keep him still; If unconscious, place the person in the recovery position.

After inhalation

Move to fresh air. Lay the affected person down, and keep her or him warm and calm. If symptoms persist, call a physician. In case of irregular breathing or respiratory arrest: Oxygen or artificial

according to Regulation (EC) No 1907/2006

BEECK Interior Stand Oil Paint

Print date: 19.03.2018 Product code: FWB_B42 Page 3 of 9

respiration, if needed.

After contact with skin

Wash contaminated skin areas thoroughly with soap and water. Remove soiled clothing. Do not use solvents or thinners. If skin irritation persists, call a physician.

After contact with eyes

Rinse with plenty of water immediately, also under the eyelids, for at least 15 minutes. Remove contact lenses, if applicable. Consult an ophthalmologist immediately.

After ingestion

Immediately give large quantities of water to drink. Do not induce vomiting.

In the event of spontaneous nausea and unconsciousness, keep the head back and bring the patient into the recovery position. Keep the respiratory tract open, prevent aspiration. Lay the affected person down, and keep her or him warm and calm. Consult a physician.

4.2. Most important symptoms and effects, both acute and delayed

May cause eye/skin irritation.

nausea, vomiting, cough, shortness of breath, abdominal pain.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment (decontamination and vital functions).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

carbon dioxide (CO2), foam, sprayed water stream or dry powder.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

The release of the following substances is possible in a fire: carbon dioxide (CO2), carbon monoxide (CO), smoke, nitrogen oxides (NOx).

The inhalation of hazardous decomposition products may cause serious health damage.

5.3. Advice for firefighters

Wear self-contained breathing apparatus for fire fighting, if necessary.

Additional information

The combustion gases are partially condensed with the water used to extinguish the fire and end up as a contaminant in this water.

Do not let product enter drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to a safe area. Provide good ventilation. Do not breathe in vapours and mist. Use personal protective equipment.

Slipping hazard due to leakage. Avoid bringing product in contact with the skin.

6.2. Environmental precautions

May not end up in waste water or open waters. Entry into rivers or surface water is to be prevented by the erection of barriers made of sand or earth or by other suitable barriers. Contact the responsible authority immediately if the product ends up in the soil, a body of water, or the sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Dispose of as described in section 13. After cleaning, flush away traces with water.

6.4. Reference to other sections

See section 8, 13

according to Regulation (EC) No 1907/2006

BEECK Interior Stand Oil Paint

Print date: 19.03.2018 Product code: FWB_B42 Page 4 of 9

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide sufficient air exchange and/or exhaust in work rooms. Containers keep tightly closed. Avoid contact with skin and eyes.

The further treatment / removal of coatings by grinding, burning, etc. may create hazardous dust and/or vapour.

Do not breathe vapours/dust. When using, do not eat, drink, or smoke.

Suitable protective equipment: See section 8.

Advice on protection against fire and explosion

Cleaning cloths, paper or other materials that are used for absorption can become a potential fire hazard. Collect and safely dispose in closed, non-flammable containers after use.

Further information on handling

Comply with the health and safety at work laws. Handle, store and transport in compliance with local regulations and in labelled containers that are suitable for this product.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in compliance with the local regulations. Store sealed in the original container.

Keep in a dry, cool place. Protect from freezing.

Advice on storage compatibility

Do not store near acids.

Further information on storage conditions

Smoking in the storage rooms is forbidden. Entry by unauthorized individuals is forbidden.

Keep at temperatures between 5°C and 25°C.

Already opened containers should be closed thoroughly and should be stored upright in order to prevent leakage.

7.3. Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
1317-65-3	Calcium carbonate, respirable	-	4		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
14807-96-6	Talc respirable dust	-	1		TWA (8 h)	WEL
1		-	-		STEL (15 min)	WEL
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL
İ		-	-		STEL (15 min)	WEL
1	ı					

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. This can be achieved by local or space exhaust. If this is not sufficient, in order to hold the solvent vapour concentration lower than the occupational exposure limit an approved respiratory protection apparatus must be worn.

according to Regulation (EC) No 1907/2006

BEECK Interior Stand Oil Paint

Print date: 19.03.2018 Product code: FWB_B42 Page 5 of 9

Protective and hygiene measures

Avoid contact with skin and eyes. Do not breathe in vapours or spray mist. Remove and wash contaminated clothing before re-use. Do not eat, drink, smoke or take snuff at work. Wash hands before breaks and immediately after handling the product. Keep away from food, drink and animal food stuffs.

Eye/face protection

Safety glasses at risk of splashing. Safety glasses with side-shields.

Eye wash.

Hand protection

Protective gloves.

The manufacturer recommends the following glove materials: PVC- or rubber gloves. Safety gloves should be selected for the actual conditions of use and in accordance with the instructions for use provided by the manufacturer.

Preventive skin protection: skin protection cream.

Skin protection

Impervious clothing, boots, apron, protective gloves.

Take off all contaminated clothing immediately. Wash contaminated skin areas thoroughly with soap and water.

Respiratory protection

When workers are facing concentrations above the exposure limit, they must use appropriate certified respirators. In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.

Environmental exposure controls

Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: white resptv. tinted

Odour: mild

Test method

pH-Value: n.a.

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

Sublimation point:

No data available.

Flash point:

61 °C

Explosive properties

No data available.

Lower explosion limits:

Upper explosion limits:

No data available.

No data available.

Auto-ignition temperature

Solid: No data available.

Decomposition temperature: No data available.

Vapour pressure: No data available.

Density: 1,25 g/cm³

according to Regulation (EC) No 1907/2006

BEECK Interior Stand Oil Paint

Print date: 19.03.2018 Product code: FWB_B42 Page 6 of 9

Water solubility: No data available.

Solubility in other solvents

No data available.

Partition coefficient:

No data available.
Flow time:

130 s / 3 mm

9.2. Other information

Solid content: No data available.

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

Stable under proper storage and handling.

10.3. Possibility of hazardous reactions

No dangerous reactions occur under normal storage conditions and in normal use. Does not polymerize.

10.4. Conditions to avoid

None under normal use.

10.5. Incompatible materials

strong oxidizers; strong acids

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

No data is available on the product itself.

CAS No	Chemical name					
	Exposure routes	Method	Dose	Species	Source	
13463-67-7	Titanium oxide					
	oral	LD50	>5000 mg/kg	rat	OECD 425	
	dermal	LD50	>5000 mg/kg	rabbit		
	inhalative (4 h) aerosol	LC50	>6,8 mg/l	rat		
68551-19-9	9 Hydrocarben, C11-C14, isoalkanes, cyclic < 2% aromatics					
	oral	LD50	> 5000 mg/kg	rat		
	dermal	LD50	> 5000 mg/kg	rabbit		
	inhalative vapour	LC50	> 5000 mg/l	rat		
1317-65-3	Calcium carbonate					
	oral	LD50	> 5000 mg/kg	rat		

SECTION 12: Ecological information

12.1. Toxicity

according to Regulation (EC) No 1907/2006

BEECK Interior Stand Oil Paint

Print date: 19.03.2018 Product code: FWB_B42 Page 7 of 9

No data is available on the product itself.

CAS No	Chemical name						
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source	
13463-67-7	Titanium oxide						
	Acute fish toxicity	LC50	>1000 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50	16 mg/l		Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50	>100 mg/l	48 h	Daphnia magna	OECD 202	
1317-65-3	Calcium carbonate						
	Acute fish toxicity	LC50	>10000 mg/l	96 h	Rainbow trout (Oncorhynchus mykiss)		
	Acute algae toxicity	ErC50	>200 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50	>1000 mg/l	48 h	Daphnia magna		

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

Further information

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Disposal in accordance with the official regulations.

Do not flush into surface water or sanitary sewer system. Offer surplus and non-recyclable solutions to a licensed disposal company.

Waste disposal number of waste from residues/unused products

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

Waste disposal number of used product

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

Contaminated packaging

Packaging can be sent for recycling after being emptied and cleaned. If recycling is not practicable, dispose of in compliance with the official regulations and the Environmental Protection (Duty of Care) Regulations 1991.

according to Regulation (EC) No 1907/2006

BEECK Interior Stand Oil Paint

Print date: 19.03.2018 Product code: FWB_B42 Page 8 of 9

SECTION 14: Transport information

Land transport (ADR/RID)

Other applicable information (land transport)

Not classified as dangerous regarding transport regulations.

Inland waterways transport (ADN)

Other applicable information (inland waterways transport)

Not classified as dangerous regarding transport regulations.

Marine transport (IMDG)

Other applicable information (marine transport)

Not classified as dangerous regarding transport regulations.

Air transport (ICAO)

Other applicable information (air transport)

Not classified as dangerous regarding transport regulations.

14.6. Special precautions for user

No data available.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): The EU limit value for this product (product category: II.A d, Lb) in ready to

use form is max 300 g/litre of VOC. The VOC content of this product in

ready to use form is max 300 g/l

Additional information

No Substances of Very High Concern (SVHC) according REACH Articel 57.

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

n.a. = not applicable

n.d. = not determined

n.d.a. = no data available

Relevant R-phrases (Number and full text)

10	Flammable.
38	Irritating to skin.

43 May cause sensitisation by skin contact.

Very toxic to aquatic organisms.

May cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

Relevant H- and EUH-phrases (Number and full text)

H226 Flammable liquid and vapour.

according to Regulation (EC) No 1907/2006

Print date: 19.03.2018	Product code: FWB_B42	Page 9 of 9
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
EUH066	Repeated exposure may cause skin dryness or cracking.	
EUH208	Contains Orange oil . May produce an allergic reaction.	

The information is based on present levels of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The product is to be used exclusively for the applications named in the technical data sheet or in the processing instructions.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)