

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BEECK Undercoat pro
Revision date : 01.08.2019
Print date : 01.08.2019

Product code : FWB_B85
Version (Revision) : 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

BEECK Undercoat pro

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Oil primer for interior and exterior.

1.3 Details of the supplier of the safety data sheet

Company name: BEECK'SCHE FARBWERKE GmbH
Street: Gottlieb-Daimler-Str. 4
Place: D-89150 Laichingen
Telephone: +49 (0) 7333 / 9607-11 Telefax: +49 (0) 7333 / 9607-10
e-mail: info@beeck.com
Contact person: Ralf Rieks

1.4 Emergency Telephone Number:

United Kingdom +44 870 600 626 / 0870 600 6266 GBK GmbH Regulatory Compliance +49(0)6132/84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02)

Signal word

Warning

Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P303+P361+P353 If on skin or hair: remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P370+P378 In case of fire: use alcohol resistant foam, carbon dioxide (CO₂), extinguishing powder, sand and water mist for extinction.

P403+P235 Store in a well-ventilated place. Keep cool.

Special rules for supplemental label elements for certain mixtures

EUH208 Contains TURPENTINE OIL ; 2-BUTANONE OXIME. May produce an allergic reaction.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BEECK Undercoat pro
Revision date : 01.08.2019
Print date : 01.08.2019

Version (Revision) : 1.0

2.3 Other hazards

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting self-closing lids, or laid out flat in a single layer to dry, or placed in a closed metal container soaked with water. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

SECTION 3: Composition / information on ingredients

3.2 Mixtures

Hazardous ingredients

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY ; REACH registration No. : 01-2119463258-33 ; EC No. : 265-150-3; CAS No. : 64742-48-9

Weight fraction : 10 - 20 %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H336

TURPENTIN OIL ; EC No. : 232-350-7; CAS No. : 8006-64-2

Weight fraction : 0,1 - 1 %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 Acute Tox. 4 ; H302 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319 Aquatic Chronic 2 ; H411

ISOTRIDECYLALCOHOL, GEETHOXYLEERD, GEFOSFATEERD, VERBINDING MET N,N-DIMETHYLCYCLOHEXANAMINE ; CAS No. : 164383-18-0

Weight fraction : < 1 %
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 Aquatic Chronic 2 ; H411

2-BUTANONE OXIME ; EC No. : 202-496-6; CAS No. : 96-29-7

Weight fraction : 0,1 - 1 %
Classification 1272/2008 [CLP] : Carc. 2 ; H351 Eye Dam. 1 ; H318 Acute Tox. 4 ; H312 Skin Sens. 1 ; H317

Additional information

Full text of R-, H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.

In case of skin contact

Change contaminated, saturated clothing. After contact with skin, wash immediately with plenty of water and soap. Clean with detergents. Avoid solvent cleaners.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BEECK Undercoat pro
Revision date : 01.08.2019
Print date : 01.08.2019

Version (Revision) : 1.0

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam Carbon dioxide (CO₂) Extinguishing powder Sand Water mist.

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

Cool endangered containers with water in case of fire. Do not allow run-off from fire-fighting to enter drains or water courses. Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment

Use personal protection equipment. Provide adequate ventilation. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean with detergents. Avoid solvent cleaners.

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode. Heating causes rise in pressure with risk of bursting. Provide earthing of containers, equipment, pumps and ventilation facilities. Avoid contact with skin and eyes. Do not inhale dust/particles. Prohibit generation/formation of mist. When using do not eat, drink, smoke, sniff.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Protect containers against damage. Keep only in the original container in a cool, well-ventilated place. Do not allow to enter into surface water or drains.

Requirements for storage rooms and vessels

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Remove all sources of ignition.

Hints on joint storage

Storage class : 3

Storage class (TRGS 510) : 3

Further information on storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Only use containers specifically approved for the substance/product.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BEECK Undercoat pro
Revision date : 01.08.2019
Print date : 01.08.2019

Version (Revision) : 1.0

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

2-BUTANONE OXIME ; CAS No. : 96-29-7

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 0,3 ppm / 1 mg/m³

Peak limitation : 8(I)

Remark : Y, H, Sh

Version : 02-04-2014

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Eye glasses with side protection.

Skin protection

Hand protection

Wear suitable gloves tested to EN374. Breakthrough time (maximum wearing time)

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values. By spraying: air fed respirator. By other operations than spraying: in well ventilated areas, airfed respirators could be replaced by a combination of charcoal filter and particulate filter mask.

8.3 Additional information

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit) , suitable respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Safety relevant basis data

Flash point :	ca.	36	°C	
Density - dependent of color: (20 °C)		1,47 - 1,5	g/cm ³	
Solvent separation test : (20 °C)	ca.	3	%	
Flow time : (23 °C)	>	200	s	ISO cup 6 mm
Viscosity : (20 °C)	ca.	900	mPa.s	
VOC-value :	ca.	295	g/l VOC	

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available.

10.3 Possibility of hazardous reactions

No information available.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BEECK Undercoat pro
Revision date : 01.08.2019
Print date : 01.08.2019

Version (Revision) : 1.0

10.4 Conditions to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

No information available.

SECTION 12: Ecological information

12.1 Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 2 for details.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

SECTION 14: Transport information

14.1 UN number

UN 1263

14.2 UN proper shipping name

Land transport (ADR/RID)

PAINT

Sea transport (IMDG)

PAINT

Air transport (ICAO-TI / IATA-DGR)

PAINT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BEECK Undercoat pro
Revision date : 01.08.2019
Print date : 01.08.2019

Version (Revision) : 1.0

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3
Classification code : F1
Hazard identification number (Kemler No.) : 30
Tunnel restriction code : D/E
Special provisions : 640E · LQ 7 · LQ 5 I · E 1
Hazard label(s) :



3

Sea transport (IMDG)

Class(es) : 3
EmS-No. : F-E / S-E
Special provisions : LQ 5 I · E 1
Hazard label(s) :



3

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3
Special provisions : E 1
Hazard label(s) :



3

14.4 Packing group

III

14.5 Environmental hazards

Land transport (ADR/RID) : No
Sea transport (IMDG) : No
Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting self-closing lids, or laid out flat in a single layer to dry, or placed in a closed metal container soaked with water. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

National regulations

Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : < 5 %

Water hazard class (WGK)

Class : 2 (Hazardous to water) Classification according to VwVwS

15.2 Chemical Safety Assessment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BEECK Undercoat pro
Revision date : 01.08.2019
Print date : 01.08.2019

Version (Revision) : 1.0

For this substance a chemical safety assessment has not been carried out.

15.3 Additional information

EU limit value for this product (cat. A/d): 300 g/l.

SECTION 16: Other information

16.1 Indication of changes

03. Hazardous ingredients · 14. Transport hazard class(es) - Land transport (ADR/RID) · 14. Transport hazard class(es)
- Sea transport (IMDG)

16.2 Abbreviations and acronyms

a.i. = Active ingredient
ACGIH = American Conference of Governmental Industrial Hygienists (US)
ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road
AFFF = Aqueous Film Forming Foam
AISE = International Association for Soaps, Detergents and Maintenance Products (joint project of AISE and CEFIC)
AOAC = AOAC International (formerly Association of Official Analytical Chemists)
aq. = Aqueous
ASTM = American Society of Testing and Materials (US)
atm = Atmosphere(s)
B.V. = Beperkt Vennootschap (Limited)
BCF = Bioconcentration Factor
bp = Boiling point at stated pressure
bw = Body weight
ca = (Circa) about
CAS No = Chemical Abstracts Service Number (see ACS - American Chemical Society)
CEFIC = European Chemical Industry Council (established 1972)
CIPAC = Collaborative International Pesticides Analytical Council
CLP = REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.
Conc = Concentration
cP = CentiPoise
cSt = Centistokes
d = Day(s)
DIN = Deutsches Institut für Normung e.V.
DNEL = Derived No-Effect Level
DT50 = Time for 50% loss; half-life
EbC50 = Median effective concentration (biomass, e.g. of algae)
EC = European Community; European Commission
EC50 = Median effective concentration
EINECS = European Inventory of Existing Commercial Chemical Substances (EU, outdated, now replaced by EC Number)
ELINCS = European List of Notified (New) Chemicals (see Tab 7, Background - Guide)
ErC50 = Median effective concentration (growth rate, e.g. of algae)
EU = European Union
EWC = European Waste Catalogue
FAO = Food and Agriculture Organization (United Nations)
GIFAP = Groupement International des Associations Nationales de Fabricants de Produits Agrochimiques (now CropLife International)
h = Hour(s)
hPa = HectoPascal (unit of pressure)
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IC50 = Concentration that produces 50% inhibition
IMDG Code = International Maritime Dangerous Goods Code
IMO = International Maritime Organization
ISO = International Organization for Standardization
IUCLID = International Uniform Chemical Information Database
IUPAC = International Union of Pure and Applied Chemistry
kg = Kilogram

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BEECK Undercoat pro
Revision date : 01.08.2019
Print date : 01.08.2019

Version (Revision) : 1.0

Kow = Distribution coefficient between n-octanol and water
kPa = KiloPascal (unit of pressure)
LC50 = Concentration required to kill 50% of test organisms
LD50 = Dose required to kill 50% of test organisms
LEL = Lower Explosive Limit/Lower Explosion Limit
LOAEL = Lowest observed adverse effect level
mg = Milligram
min = Minute(s)
ml = Milliliter
mmHg = Pressure equivalent to 1 mm of mercury (133.3 Pa)
mp = Melting point
MRL = Maximum Residue Limit
MSDS = Material Safety Data Sheet
n.o.s. = Not Otherwise Specified
NIOSH = National Institute for Occupational Safety and Health (US)
NOAEL = No Observed Adverse Effect Level
NOEC = No observed effect concentration
NOEL = No Observable Effect Level
NOx = Oxides of Nitrogen
OECD = Organization for Economic Cooperation and Development
OEL = Occupational Exposure Limits
Pa = Pascal (unit of pressure)
PBT = Persistent, Bioaccumulative or Toxic
pH = -log₁₀ hydrogen ion concentration
pKa = -log₁₀ acid dissociation constant
PNEC = Previsible Non Effect Concentration
POPs = Persistent Organic Pollutants
ppb = Parts per billion
PPE = Personal Protection Equipment
ppm = Parts per million
ppt = Parts per trillion
PVC = Polyvinyl Chloride
QSAR = Quantitative Structure-Activity Relationship
REACH = Registration, Evaluation and Authorization of Chemicals (EU, see NCP)
SI = International System of Units
STEL = Short-Term Exposure Limit
tech. = Technical grade
TSCA = Toxic Substances Control Act (US)
TWA = Time-Weighted Average
vPvB = Very Persistent and Very Bioaccumulative
WHO = World Health Organization = OMS
y = Year(s)

16.3 Key literature references and sources for data

None

16.5 Relevant R-, H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H302+H312+H332	Harmful if swallowed, in contact with skin or if inhaled.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BEECK Undercoat pro
Revision date : 01.08.2019
Print date : 01.08.2019

Version (Revision) : 1.0

R10	Flammable.
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
R21	Harmful in contact with skin.
R36/38	Irritating to eyes and skin.
R40	Limited evidence of a carcinogenic effect.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
